

INTERIOR USL-SQR2F
Internal Fixture Retrofit Kit




Interior


Dry Location


Dimmable


AC


Down Light


Up Light


5 Year
Warranty



OVERVIEW

This square light is ideal for retrofitting surface mount fixtures in a wide range of diameters. The light engine fits round and square fixtures with diameters of anywhere from 6 to 16 inches with a depth of as little as 2 inches. This versatility helps reduce the amount of inventory needed.

FEATURES

- TRIAC dimmable 5-100%
- PF>0.9
- THD<20%
- Retrofit ceiling fixtures and wall sconces
- Fits round and square fixtures
- AC direct drive on integrated LED board
- Integrated heat sink



ORDERING INFORMATION

EXAMPLE PN: USL-SQR2F-10W-27K

USL-SQR2F	POWER	CCT	DIMMING/VOLTAGE
8W	8 WATTS	27K	2700K
10W	10 WATTS	30K	3000K
12W	12 WATTS	40K	4000K
15W	15 WATTS	50K	5000K
17W	17 WATTS		
20W	20 WATTS		
23W	23 WATTS		
25W	25 WATTS		
28W	28 WATTS		
30W	30 WATTS		
32W	32 WATTS		

INTERIOR USL-SQR2F

Internal Fixture Retrofit Kit



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-SQR2F	100-277V	-4°F – 104°F -20°C – 40°C	50,000 HOURS	2700K, 3000K 4000K, 5000K	80+	90-100 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)	FIXTURE DIAMETERS
USL-SQR2F-8W	8	720	90	6-9 in
USL-SQR2F-10W	10	900	90	6-9 in
USL-SQR2F-12W	12	1,080	90	6-9 in
USL-SQR2F-15W	15	1,500	100	8-11 in
USL-SQR2F-17W	17	1,700	100	8-11 in
USL-SQR2F-20W	20	2,000	100	11-14 in
USL-SQR2F-25W	25	2,500	100	11-16 in
USL-SQR2F-30W	30	3,000	100	13-16 in

DIMENSIONS

MODEL	L LENGTH	H HEIGHT
8-12W	4.7 in 120 mm	0.5 in 13 mm
15-17W	5.9 in 150 mm	0.6 in 15 mm
20-25W	7.1 in 180 mm	0.6 in 15 mm
28-32W	8.3 in 211 mm	0.6 in 15 mm

