

EXTERIOR USL-CWPIA
Classic Wall Pack



PROJECT		TYPE		DATE	
---------	--	------	--	------	--



Exterior



Wet Location



Non-Dimming Dimmable



10V



AC



Down Light



5 Year Warranty



OVERVIEW

US Luminaire's second generation classic wall pack has improved efficacy and reduced weight. It is suitable for mounting to j-box or surface mounting. Select models are dimmable. Please see specification table for details.

FEATURES

- Sealed die-cast body
- Polycarbonate lens with UV stabilizers
- Optional photocell
- Replaces 100-400W MH
- Select models are 0-10V dimmable



ORDERING INFORMATION

EXAMPLE PN: USL-CWPIA-40W-LV-50K-D-0

USL-CWPIA	POWER	VOLTAGE	CCT	FINISH	PHOTOCELL
	30W 30 WATTS	LV 120-277V	40K 4000K	D DARK BRONZE	0 NONE
	40W 40 WATTS	HV 347-480V	50K 5000K	B BLACK	P0 120-277V PHOTOCELL
	65W 65 WATTS			W WHITE	
	90W 90 WATTS				
	125W 125 WATTS				

*Note: 30W is only available with 120-277V AC

EXTERIOR USL-CWPIA

Classic Wall Pack



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-CWPIA	120-277V AC 347-480V AC	-40°F – 104°F -40°C – 40°C	50,000 HOURS	4000K, 5000K	70+	111-128 lm/W

MODEL	POWER (W)	MH EQUIVALENT	DIMMABLE MODELS		LUMENS (lm) ±10%		EFFICACY (lm/W)
			LV	HV	4000K	5000K	
USL-CWPIA-30W	30	100W MH	—	✓	3,550	3,600	118-120
USL-CWPIA-40W	40	175W MH	—	✓	5,000	5,100	125-128
USL-CWPIA-65W	65	250W MH	—	✓	7,800	7,990	120-123
USL-CWPIA-90W	90	320W MH	✓	✓	10,000	10,500	111-117
USL-CWPIA-120W	120	400W MH	—	✓	14,500	15,000	121-125

DIMENSIONS

MODEL	W1 MAX WIDTH	W2 WIDTH	D DEPTH	H HEIGHT	WEIGHT
USL-CWPIA-30W					6.3 lb 13.9 kg
USL-CWPIA-40W					6.5 lb 14.4 kg
USL-CWPIA-65W	14.21 in 361 mm	13.07 in 332 mm	7.2 in 183 mm	9.25 in 253 mm	6.7 lb 14.8 kg
USL-CWPIA-90W					7.3 lb 16.1 kg
USL-CWPIA-120W					8.2 lb 18.0 kg

