

INTERIOR USL-TRAI F

Architectural Troffer



Interior Damp Location Dimmable 5 Year Warranty

OVERVIEW

This troffer is available in three different sizes: standard 2x2 and 2x4 and also 1x4. This allows one fixture to work in more applications, creating a uniform look in any building.

FEATURES

- 0-10V dimmable
- Emergency backup available
- Motion sensor available
- IP20
- Damp location listed
- 1x4 size available



ORDERING INFORMATION

EXAMPLE PN: USL-TRAI F-2X2-40W-LV-40K-10V-0

USL-TRAI F	SIZE / POWER*	VOLTAGE	CTT	DIMMING	OPTIONS*
	2X2-27W 2X2 FT, 27 WATTS	LV 100-277V	30K 3000K	10V 0-10V	0 NONE
	2X2-40W 2X2 FT, 40 WATTS		35K 3500K		OS OCCUPANCY SENSOR
	2X4-40W 2X4 FT, 40 WATTS		40K 4000K		
	2X4-62W 2X4 FT, 62 WATTS		50K 5000K		
	1X4-40W 1X4 FT, 40 WATTS				

*Note: 1x4 fixture is not DLC listed.

ACCESSORIES

USL-TRAI F-ACC	ACCESSORY
----------------	-----------

EM Emergency battery

INTERIOR USL-TRA1F

Architectural Troffer



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	OPERATING TEMPERATURE	RATED LIFESPAN	CCT	CRI	EFFICACY
USL-TRA1F	120-277V AC	-4°F – 104°F -20°C – 40°C	50,000 HOURS	3000K, 3500K, 4000K, 5000K	80+	100 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)	DLC			
				3000K	3500K	4000K	5000K
USL-TRA1F-2X2-27W	27	2,700	100			✓	✓
USL-TRA1F-2X2-40W	40	4,000	100			✓	✓
USL-TRA1F-2X4-40W	40	4,000	100			✓	✓
USL-TRA1F-2X4-62W	62	6,200	100	✓	✓	✓	✓
USL-TRA1F-1X4-40W	49	4,000	100				

DIMENSIONS

MODEL	L	W	H
USL-TRA1F-2X2	23.82 in 605 mm	23.82 in 605 mm	3.94 in 100 mm
USL-TRA1F-2X4	47.72 in 1212 mm		
USL-TRA1F-1X4		11.17 in 284 mm	3.96 in 101 mm

