

INTERIOR USL-HBC1E

Sunflower High Bay



Interior



Dimmable



Wet Location



Down Light



5 Year Warranty



DLC




ETL

OVERVIEW


This light-weight, compact high bay fixture is ideally suited for large area applications such as workshops, warehouses, parking lots, sports venues and dock areas. Its unique patented sunflower heat sink allows for advanced thermal dissipation. And its rugged die-cast aluminum housing ensures its durability, proven by its 5-year warranty.

FEATURES

- IP65
- Anti-corrosion coating surface
- Special high reflectivity coating allows for lighter weight, softer light and high efficiency
- Meanwell power supply offers high reliability and efficiency
- Quick and easy installation



Hook



Bracket

ORDERING INFORMATION

EXAMPLE PN: USL-HBC1E-100W-LV-50K-10V-90-H

USL-HBC1E	POWER	VOLTAGE	CCT	DIMMING	BEAM ANGLE	BEAM ANGLE
	100W 100 WATTS	LV 100-277V	30K 3000K	0 NONE	90 90°	H HOOK
	120W 120 WATTS		50K 5000K	10V 0-10V	120 120°	B BRACKET
	150W 150 WATTS					
	200W 200 WATTS					

INTERIOR USL-HBCIE Sunflower High Bay



SPECIFICATIONS

MODEL	OPERATION VOLTAGE	AMBIENT OPERATING TEMP	RATED LIFESPAN	CRI	CCT	EFFICACY
USL-HBCIE	100-277V AC	-40°F – 122°F -40°C – 50°C	100,000 HOURS	75+	3000K, 4000K 5000K	150 lm/W

MODEL	POWER (W)	LUMENS (lm)	EFFICACY (lm/W)	MH REPLACEMENT (W)	WEIGHT
USL-HBCIE-100W	100	15,000	150	250	9.5 lbs 4.3 kg
USL-HBCIE-150W	150	22,500	150	400	10.1 lbs 4.6 kg
USL-HBCIE-200W	200	30,000	150	600	11.9 lbs 5.4 kg

DIMENSIONS

	100W	150W/200W	DIMENSIONAL DRAWINGS
D DIAMETER	14.2 in 360 mm	14.2 in 360 mm	
H HEIGHT	9.2 in 234 mm	9.3 in 236 mm	

PHOTOMETRICS

